



QUOTATION

City of Dania Beach  
 Robert Baldwin  
 100 West Dania Beach Blvd  
 Dania Beach, FL 33004

Wheeled Coach Industries, Inc  
 Bill McCorkle

Quote No: BSO16-0001  
 T9 - 170: 290170 Model: Type 9 - 180" Module, Custom  
 T9 - 170: 0999015 International, (SO) 180" Module, Custom  
 T9 - 170: 200060 Type 9 - 180" Module, Custom Series

WO#:

Page 1

PART NO	DESCRIPTION	QTY
	<b>= International, (SO) 180 Module, Custom - 619.002 06/01/12 ==</b>	<b>1</b>
	Eng to reference drawings. *** Vertical exhaust pipe, passenger side ***	
	<b>CHASSIS:</b>	<b>1</b>
00-90-2120	2016 International, 4300 LP 4x2 SBA 2-Door (SO-CHASS-)	1
	260HP - 660FTLB Allison 3000 Air brakes 175"WB 10k front 15.5k rear suspension 22.5 Steel wheels Premium cab interior package Seats Inc 911 air susp driver and passenger	
	*** Vertical exhaust pipe, passenger side *** Turn the vertical exhaust outlet to exit 90 degree outboard	
	<b>CAB TO MODULE MOUNTING:</b>	<b>1</b>
10-11-1000	Bellows, Walkthru, Unigrip, Cab Height, Int'l, Custom (SO-WT-359027)	1
	Custom width and height. Eng: ref Sarasota #309009 for required height and width of opening. Transition plate to be diamond plate.(not rubber coated)	
15-10-0000	BASE BILL OF MATERIALS	1
15-11-9872	2015, Base, International,180" Module, Standard Model 2015-5 (BASE-359007) SR #213314F	1
	<b>CHASSIS ADD-ONS:</b>	<b>1</b>
1A-10-0100	Lettering/Graphics, By Outside Vendor (SO-LETTR-359027)	1
	Location: 24/7	
1A-10-SR00	Radio/Motorola radio installationn By Outside Vendor SR# 215744_	1
	Installation of Motorola APX7500. Ashtin to do installation at WC. (1) Bracket mount Motorola radio head on forward cab console panel.	

PART NO	DESCRIPTION	QTY
	(1) Bracket mount Motorola radio head on wall beside C/S rear A/A panel.	
	(1) Radio base unit	
1A-10-SR01	Mobile radio, Motorola SR#215744F Motorola APX7500 Dual Band - per attached quote QU329512 Qty 1 (Sales Jonoathan Franklin jf@signalcommunications.com 954-275-8854 Motorola APX7500 Dual Bank Mid Power Radio	1
1A-10-SR02	Portable Radio(s), Motorola SR#215744F  Motorola APX7000 Portable per attached quote QU323615 Qty 1 (Sales Jonoathan Franklin jf@signalcommunications.com 954-275-8854	3
	<b>SUSPENSION:</b>	1
1F-30-7900	Auto Dump w/override Sw, For Air Suspension dump feature to be activated by left rear entry door. Override sw to be recessed in cabt near right rear entry door.(mica recess ilo ABS). Ignition switch hot, std.  Air suspension system will deflate when: Streetside rear door is opened and override switch is off.  Air suspension system will inflate when: Streetside rear door is closed or vehicle is placed in gear or when override switch is activated.	1
1F-31-4010	Suspension, OEM, Installed, Int'l, w/OEM Sw in Dash Only to dump in neutral w/park brake set. OEM air gauge in dash. OEM automatic heated expello valve	1
	<b>ALTERNATOR(S):</b>	1
1K-40-5000	Alternator,OEM L/N 320 amp	1
	<b>THROTTLE CONTROLS:</b>	1
1P-50-5520	High Idle Controls, OEM, Int'l High idle to activate automatically with low voltage. (per WC std Int'l chassis program)	1
	<b>CAB STEP:</b>	1
20-60-2010	Cover, Fuel Tank, Dia Plate, INTL, Custom (SO-FUEL-359007)  Dia Plate cover with steps like Longwood #319040	1
	<b>CHASSIS ADD ONS, MISC</b>	1
2F-71-3710	Highbeam Flasher, Diamond Logic, Dual Mode Dual Mode High Beam Flasher, with SPST switch.  Set for Mode 2: Alternating 80 FPM, Simultaneous 80 FPM, Double Flash 120 FPM	1
	<b>BUMPER MARKERS:</b>	1
4F-12-4050	Bumper Pole Markers, Bore, Lighted, Int'l, Installed	1
	<b>HEATING/AIR CONDITIONING:</b>	1
5U-12-1000	Hoses, Silicone, to the Rear Heater (1001045)	1

PART NO	DESCRIPTION	QTY
5U-20-0300	Heater Hoses, Insulated to Rear, IATS Wrap insulation around heater hoses front to rear.	1
5U-70-08SR	Heat/AC, Int'l, Coolbar, LF Location (SO-AC-359027) SR #212855F  Per Eng design See SR. Mounted in upper left corner of module, at 45 degree angle.  Heat/AC, Int'l, Combo, w/Coolbar  Use (2) rear vista displays to control Hoseline 12vdc heat/ac unit. VMux system to be ignition hot and restart heater or AC to previous setting.  External condenser mounted in the COOL-BAR on the front of the box.  Connected to add'l OEM A/C compressor  Rear Heat / AC to be master switch hot.  with 12" x 12" filter at air intake location. (Black Supply, Return Air Register 12" x 12" To include (1) 12" x 12" filter.	1
5U-70-09SR	AC,Danhard, 50-2000, 110V, IATS (SO-AC2-359027) SR#214380F  Danhard m/n 50-2000 110v AC system mounted in upper "J" area. 20amp shoreline inlet picked separately.  Mount Danhard condenser, compressor & dryer below module. Ref pictures supplied by customer.  Control module location to be determined by Eng.  No heat requirements.	1
<b>BATTERY SWITCHES:</b>		1
60-22-1080	Battery Sw, 5min Timer, Int'l, Fig 5B Activated thru OEM ignition switch timer function upon ignition "off". Momentary rocker switch, on driver's side of cab console, to function as timer shutoff and also reactivate timer.  (3) OEM batteries in slideout tray below driver's door.  ONLY Module power is turned on/off. Chassis power is NOT turned off.	1
<b>BATTERY TRAY:</b>		1
60-40-2500	Tray,(2-4) Battery,Slide-Out,(2)Gator Grip Steps, Std, Int'l w/turtle-tile installed in bottom of tray	1
<b>CONSOLES:</b>		1
7U-10-0002	Vista Display, Curbside Wall, ILOS (SO-CABT-359007) SR #212855F  Low profile console for the Vista display.(no thermostat) This will be mounted on CS wall at head of sq bench area, just rearward of the C/S entry door header.  All switches to be in Vista display except A/A light.	1

PART NO	DESCRIPTION	QTY
7U-12-5010	Console, Floor, Custom, Alum, Rubber Coated Back (SO-CONS-359027) new code	1
	per Eng design.	
	with cup holder, map storage, & space for MDT mount.	
	<b>SIREN SPEAKERS:</b>	1
DF-10-6112	Speakers, Cast, in Bumper, Int'l, Std, 2008+	1
	<b>WHEELCOVERS INSTALLED:</b>	1
X5-10-1500	Wheelcovers, Phoenix, Installed, Int'l, 22.5" Wheels (SO-CVRS-359007)	1
	with Air Max Valve Extenders, std	
	<b>== Type 9 - 180" Module, Custom Series - 618.080 06/18/08</b>	1
2U-77-3000	Undercoating, Type 9	1
35-05-0300	Type 9 - 180" Module - Custom Series 180" Body	1
35-05-0310	Type 9 - 180" Module General Body Construction Spec 180" Body	1
35-05-0320	Type 9 - 180" Module Vehicle Body Structure Spec 180" Body	1
35-05-2000	INTERIOR CABINETS -Duralite Construction, Wood	1
	<b>MODULE BODIES:</b>	1
35-10-0064	Aisle Space, per KKK, STD approx 45" (gain of an inch compared to #359007)	1
	Install anti-slip decal with Wheeled Coach logo on curbside and rear stainless steel thresholds, STD	
	Add grip tape to the first step on curbside entry door	
35-10-00SR	96" body width with 45" aisle width (BODY-359027)	1
	Eng: Ref #359007. There are changes to compts "A", "B", & "D". Size of walkthru opening to cab to be increased. Wheelwells need to be designed for 22.5" wheels.(please advise which compts or cabts will be affected by wheelwell change prior to release)	
35-10-0960	Headroom, 72" H.R. Type 9 - 170" module, Std Model	1
35-10-SR09	Exterior Compartments to be .125" All Exterior Compartments are to be constructed of .125" Aluminum Thickness, Std on MAV	1
35-11-0300	Drop Skirt, 6 inches forward of rear wheels, Both sides	1
37-00-0350	Coating, Scorpion X02, Per Compt, (1), Std Light Gray	5
	COMPTS A, B, D, E, & F	
37-00-0360	Coating, Scorpion, Rear Bumper Supports the entire steel structure of rear bumper.	1
37-00-0710	Duraseam Doors, with Hidden Jambs	1
	Magnetic door switches, STD	
37-00-0900	Compartments, Std, Floor 3" Drop Down from Door Opening, MAV compt "B"	1

PART NO	DESCRIPTION	QTY
37-00-0900	Compartments, Floor 4" Drop Down from Door Opening, ILOS (SO-DROP-359007)  4" dropdown ilos, compt "D".(ref Margate)	1
37-00-1000	Compartments, Sweepout , MAV  compts "A" , "E" & "F"	3
38-00-SR01	Drip rails, Screw & VHB Tape, ILOS (SO-DRIP-359007) SR #213292F  Install two screws, one each side outboard, on modular door drip rails IAT adhesive	1
3C-00-0000	Type 9 - 180" Module, EMS With 0.125" module skins.  All Exterior Compartment venting shall be a stamped (Louvered) style, coated to match the compt interior finish, std.  All compt floors to have addtl 1" x 2" floor reinforcement.  Module to be 96" wide, skin to skin, ilos.	1
3D-A0-06SR	A, Compt, Custom, 180" Module, T9 (SO-A-359027) SR# 213314F new code !!!  C/S entry door moved forward, A moved to rear of CS entry Double door.  Eng: reduce depth of this compt by 1/2"(compared to unit #359007) to allow S/B to be reduced for addtl 1" of aisle space.	1
3D-B1-0450	B1, Compt, Widened and Raised, 180" Module, T9, 72" H.R (SO-B-359027) SR #211888F new code !!  widened and raised, double doors B2 deleted  Eng: reduce depth of this compt by 1/2"(compared to unit #359007) to allow S/B to be reduced for addtl 1" of aisle space.	1
3D-B2-0200	B2, Compt, Deleted	1
3D-D0-06SR	D, Compt, Custom, 180" Module, T9 (SO-D-359027) SR #211888F new code !!!  Full height Approx 44"W, double doors Eng: approx 21" deep, ilos.  Full height compt "D" with upper closeout for Danhard unit and access from compt "D" for servicing AC unit.  Drop pan fwd LBB section to accomodate 74" backboards per previous re-engineering	1
3D-E0-02SR	E, Compt, Custom, 180" Module, T9 (SO-E-359007) SR #211888F  With Double Doors  Eng: approx 21" deep, ilos.	1

PART NO	DESCRIPTION	QTY
	form the wireguard around the components mounted on the ceiling to allow for use of adjustable shelf	
3D-F0-03SR	F, Compt, Custom, 180" Module, T9 (SO-F-359007)	1
	Full height, w/dogleg and access panel for A/C unit.	
	Eng: approx 21" deep, ilos.	
	compt opening to be the same height as compt "D".	
	<b>EXTERIOR DIVIDERS:</b>	
3F-10-0002	Divider, Vertical, 3/16" Thick, Adjustable (SO-DIV-359007)	1
	3/16" rubber coated aluminum.	
	Two (2) Compt D, approx full depth, between wall #1 and fixed divider.	
	Rubber coated.	
3F-10-1100	Divider, Vertical, 3/16" Thick, Custom in compt D, approx full depth, center	1
	rubber coated	
	<b>SHELF- COMPARTMENT "A"/RF CABINET:</b>	
3F-20-5500	Shelf, Custom, Cmpt "A", (1), W/Unistrut Track w/galvanized steel shelf track, ILOS.	1
	Full Width and Depth, equally spaced above SCBA brackets	
3F-20-6000	Shelf, Custom, Cmpt "A", (1), Add, W/Unistrut Track w/galvanized steel shelf track, ILOS.	1
	Full Width and Depth, equally spaced above SCBA brackets	
	Unistrut track to be installed top to bottom, to also be used to mount SCBA brackets on a plate.	
	<b>SHELF- COMPARTMENT "D":</b>	
3F-40-5500	Shelf, Custom, Cmpt "D", (1), W/Unistrut Track w/galvanized steel shelf track, ILOS.	1
	3/16" mill finish aluminum.	
	both between rear divider and wall #3, equally spaced.	
3F-40-6000	Shelf, Custom, Cmpt "D", (1), Add, W/Unistrut Track w/galvanized steel shelf track, ILOS.	2
	3/16" mill finish aluminum.	
	both between rear divider and wall #3, equally spaced.	
	<b>SHELF- COMPARTMENT "E":</b>	
3F-50-7000	Shelf, Custom, Cmpt "E", (1), W/Unistrut Track w/galvanized steel shelf track, ILOS.	1
	3/16" mill finish aluminum.	
	equally spaced	

PART NO	DESCRIPTION	QTY
3F-50-7500	Shelf,Custom,Cmpt"E", (1),Add,W/Unistrut Track w/galvanized steel shelf track, ILOS.  3/16" mill finish aluminum.  equally spaced	1
<b>SHELF- COMPARTMENT "F":</b>		1
3F-60-6000	Shelf, Custom, Adj, Cmpt "F", (1) 3/16" mill finish aluminum.  above O2	1
<b>COMPARTMENT / SHELF, MISC:</b>		1
3F-70-1200	Upgrade,Shelf/Div to 3/16",W/1" Lips, ILOS Location: A - (2) D - (3) E - (2) F - (1)	8
3F-70-1710	Reinforcement, Compartment Wall, For SCBA Bracket compt "B", wall #1 compt "F", wall #1	2
3F-70-18SR	Plate, Alum, For SCBA Bracket to Mount on Unistrut Track (SO-PLATE-359007) SR #214436F  compt "A", wall #1	1
<b>WINDOWS:</b>		1
3P-10-5201	Window,Upper,CS/Slider,Rr/Fixed,Priv Tint,PAN,Std Model only	1
<b>MODULE ENTRY DOOR HANDLES:</b>		1
3U-30-8010	Handles, Patient Entry, Trimark, Chrome "SafePass" ILOS	1
<b>EXTERIOR COMPT DOOR HANDLES:</b>		1
3U-40-0512	Handle, Module Compt, Trimark, Chrome, ILOS	5
3U-40-0514	Latch, Paddle, Trimark, For Trailing Door compts "A", "B1", "D", & "E"	4
3U-60-0100	ELECTRIC DOOR LOCK PACKAGE OPTIONS: Click to add	1
3U-60-1390	Door Locks,Electric, Trimark, (1)DOOR, Entry Door  Module entry doors.	2
3U-60-1400	Door Locks,Electric, Trimark, (1)DOOR, Compt Door  compts "A", "B", "D", "E", & "F"	5
<b>ELECTRICAL LOCKS SWITCHING:</b>		1
3U-60-1500	Switch,Momentary Rocker,Activate Elect Door Locks (1) recessed in cabt near right rear entry door, per CA's (1) on bulkhead wall by C/S entry door.	2
3U-60-2500	Switch, Stealth, Cab/Mod Doors (not Dodge) In grille on passenger's side.	1
3U-60-3000	Relay Control Circuit, Electric Locks	1
3U-60-5200	Circuit, OEM Door Lock to activate Mod Doors(not Dodge)	1
3U-70-0000	Keypad, Numeric, Wireless, Electric Door Locks (includes PLRB-RC)  (1) rear of module, passenger side. (1) front module, by driver door, (1) on RF compt door	3

PART NO	DESCRIPTION	QTY
	If possible, set unlock key code to ***2014***	
	<b>DOOR HOLD OPENS:</b>	<b>1</b>
	comment: Side Entry Door to have heavy duty spring hold open device!!!	
40-10-1050	Hold Open, Cast, Grabber (1), 3 in., ILOS (1) compt "A", trailing door (1) compt "B", trailing door (1) compt "D", leading door	3
40-10-1611	Hold Opens,Rr Doors,Cast,Grabber (2), 5.5", Std Model only - Installed so doors will open as wide as possible - Mount at bottom of doors due to camera	1
40-10-7202	Hold Open, Spring Activated Door Prop, 11", (1) Each, ILOS 11" Door Prop, ILOS (#HA24003) !!!!  Compt A - 1, leading door Compt B - 1 Compt D - 1, trailing door Compt E - 2 Compt F - 1	6
40-10-7500	Rubber Bumpers, (2), IATS Inside edge of double door flange ILO 3/8" bumpers on following double door compartment doors:  A, D, E	2
	<b>DOOR PANELS:</b>	<b>1</b>
45-10-44SR	Panels, Entry, Durasafe, Stainless Steel, No Chevrons !! (SO-PNL-311195)  Durasafe Design  Aluminum Center Panels. NO CHEVRONS!!(24/7 to install)	1
	<b>FENDER FLARES:</b>	<b>1</b>
4A-10-1000	Flare, Fender, Rear, Black Rubber	1
	<b>BUMPERS:</b>	<b>1</b>
4F-10-0001	Strips, Nylon, On Bumper Step and Kickplate (SO-NYLON-319040)  For rear bumper flip-up step, rear & bottom facing edges, and kickplate below entry doors, to protect cot when loading	1
4F-11-30SR	Rubrail,Rubber,Full Length of Front Bumper (SO-BUMPR-289044) SR#210826F  Full length front dock bumper from bumper end to bumper end, through-bolted  Install double thickness between bumper mounting bolts	1
4F-12-0002	Bumper,Rear,Frtlnr/Int'l,Std,W/Skids & w/LED DOT lights, St (not C4500)  w/ Gator Grip on flip up step. Reinforced, std on MAV	1
4F-12-1000	Dock Bumpers, 3 - Hole, Black, on Rear	1
	<b>SKIRTRAILS</b>	<b>1</b>
4U-10-9210	Skirtrails,Extruded Rubber w/Refl Tape,170-175" Module	1



PART NO	DESCRIPTION	QTY
4U-10-9500	Tape, Reflective, White, For Extruded Rubber Skirtrails	1
<b>STONE GUARDS (FRONT):</b>		<b>1</b>
4U-11-7100	Stone Guard, Frt, Diamond Plate, 24", Int'l	1
<b>KICKPLATES (w/STD. REAR STONEGUARDS):</b>		<b>1</b>
50-10-0001	Kickplate W/ Recess, LED Tag Lights, Mill Finish, w/Warn Lts (SO-KICK-359007) SR#211888F	1
Mill finish for full Chevrons (24/Seven ) Tag recess in center.		
No Stop/Tail, Turn or Back-Up Lights on K/Plate.		
<b>MODULE ADD-ONS:</b>		<b>1</b>
55-10-3000	Holder, License Plate, Cast, C30002, STD - in rear kick plate, centered	1
55-10-4300	Storage, SCBA Cylinder, Door, (1) Two (2) one each side of rear wheelwell, on str/s One (1) rear of rear wheelwell on c/s.	3
**Engineering to review compt & warning/turn light conflicts		
55-30-4000	Sill Protectors, Stainless, All Compts	1
55-30-40SR	Sill Protectors, Stainless, Add'l, Custom (SO-SILL-359041) new code	1
on outer edge of C/S door, compts "D" & "F"		
<b>MODULE STEPWELL:</b>		<b>1</b>
55-90-6030	Stepwell, Double Step, ILOS, MAV	1
<b>MUD FLAPS:</b>		<b>1</b>
5A-10-1001	Mud Flaps, Rear, W/Logo, Std Model only	1
<b>PAINT/BELTS:</b>		<b>1</b>
5F-10-3600	Paint, Multi-Color, Labor Charge	1
5F-10-3700	Paint, Entire Units, MAV Units, Red &/or Metallic Top part of module from under the warning lights up to the roof extrusions and drip rail to be Black- FLNA 40119 including CoolBar (ref Margate #311195) No black paint on rear module skin due to chevron !!! The remainder of module to be Red-FLNA 30484.	1
The cab below the door window to include the body line across front fenders to be Red-FLNA 30484.		
The cab roof, A & B pillars, and hood to body line be Black- FLNA 40119 (see reference photos attachment D on server).		
Paint mod roof skin Ford white: FA91:YZ.		
5F-10-49SP	Paint, Mod Roof Area, white. (SO-PNT2-341096) SR#2131018	1
Module roof extrusions, drip rail and up to be Ford FA91:YZ !!! White		
<b>PINSTRIPE: - PER ROLL</b>		<b>1</b>
5K-10-5100	Pinstripe, Black, Non-Reflective, 1/4 In	1
<b>DECAL PACKAGES INSTALLED:</b>		<b>1</b>
5P-10-5001	Roof Star, White Border, Installed, Std Model Only	1
<b>ELECTRICAL SYSTEM: Circuitboard</b>		<b>1</b>
<b>COAX CABLES/ANTENNAS:</b>		<b>1</b>
65-30-6500	Base- Antenna, Motorola Mount, W/Coax (1) port #1, behind pass seat, tagged for 800mhz antenna (1) port #2, in Str/s action area, tagged for UHF antenna	2

PART NO	DESCRIPTION	QTY
<b>12VDC POWER SOURCES &amp; OUTLETS:</b>		
6A-22-200E	Outlet, Cigar Lighter, STD, (2), A/A on 20amp circuit, Constant Hot, ILOS.	1
6A-22-2500	Outlet, Cigar Lighter, IATS, (1) (3) Ignition switch hot (1)RF cabinet, upper, near 110vac outlet that is near wall #3. (in ceiling of closeout/dogleg may be the best option) (2)Center console, Pass side, facing dash  (1) Master switch hot (1)Center console, for spotlight (best location)	4
6A-22-5200	Outlet, Kussmaul, USB Dual Port, 5VDC, 3 Amp output, switch panel Style, ILOS ignition hot.  on top of cab console, to right of Firecom control, per Eng panel design.	1
6A-22-5250	Outlet, Kussmaul, USB Dual Port, 5VDC, 3 Amp output, switch panel Style, IATS ignition hot  in Str/s action area, outlet panel	1
<b>POWER SOURCE, 12 VDC</b>		
6A-23-0910	Power Source, 12VDC, 20A, Ignition/Shoreline Hot 20amp 12 volt DC circuit ran to two locations, (1) pre-wire coil and tagged in action area and (1) pre-wire coil and tagged behind driver's seat.	1
6A-23-2200	Power Source, 12 VDC, 20 Amp (+-) (3) For streamlight charger power (customer installed) Constant hot. (1) RF Compt "A", thru ceiling near compt opening, by wall #3. Coil & tag With 3' pigtails (1) lower bulkhead area, Coil & tag with 6' tails, (1) Compt B, wall #3 centered under closeout. Coil & tag With 3' pigtails (1) in compt "E", Constant hot, upper wall #1.	4
6A-23-3000	Power Source, 12 VDC, 30 Amp (+-) (1) Ignition Hot, to terminate in center console, at buss bars, (hot and ground). (1) Constant Hot, to terminate behind Str/s A/A, w/6 foot tails (hot and ground). (1) Ignition Hot, to terminate behind Str/s A/A, w/6 foot tails (hot and ground).	3
6A-23-3001	Power Source, 12 VDC, 30 Amp (+-), Std Model only Constant Hot, to terminate in center console, at buss bars, (hot and ground).	1
<b>BUSS BARS</b>		
6A-24-1100	Buss Bar Assembly (+/-), 5 Position, inside cab console, for 30amp power source	1
<b>ELECTRICAL ACCESSORIES</b>		
6E-10-SR13	Refrigerator, Norcold, 12vdc, DE0740BB, 110vac/12vdc (SO-FRIG-311195) #SR#212959F  Ign hot and thru shoreline  mounted above RF cabt "E", per CA drawings.  Door to be hinged on left.	1

PART NO	DESCRIPTION	QTY
	Add alum trim under fridge	
6E-10-SR26	Knox MedVault 2 w/WiFi (SO-KNOX-359007) SR #2013119F	1
	Mech Eng to design RF cabt "E" to house Knox box, per CA drawings. Elect Eng to run wire to this area.	
	<b>SHORELINE INLETS:</b>	1
6F-80-5400	Shoreline Indicator Light, 110VAC, LED, Green	2
	on rear of module, (1) near each shoreline inlet	
6F-90-4105	Super Auto Eject, 20 amp, ILOS, Red, Std Model Only rear of module, above left tail-light housing	1
6F-90-4106	Super Auto Eject, 20 amp, ILOS, Blue, IATS (SO-INLET-359027)	1
	For 110vac system.	
	rear module, above left tail-light housing	
6F-90-41SR	Labels, Shoreline Inlets (SO-LABEL-359027)	1
	(1) _____ - Danhard 110VAC A/C Unit.....	
	(1) AS99004 - outlets, inverter/charger.....	
	<b>110 VAC OUTLETS:</b>	1
6K-40-1000	Outlet, 110 VAC, Duplex, (2), STD (1) outlet in action area (1) rear wall at foot of S/B, down low.	1
6K-40-20SR	Outlet, 110 VAC, 28" Power Strip (SO-STRIP-359007) SR #214436F	1
	Grainger #15X730 24" Power Strip, 8-Port	
	in A/A, per reference drawings	
6K-40-6200	Outlet, 110VAC, Interior, T-Box,w/ S/S Cover, Mods (1) RF Compt "A", upper wall #1, near door opening. (1) RF Compt "A", upper wall #3, near door opening.	2
	<b>INVERTERS:</b>	1
7F-10-9000	Inverter/Charger, Vanner 20-1050CUL-DC Mounted on ceiling in compt "E"	1
	<b>GAUGES/METERS:</b>	1
	Alarm, Low Voltage, Audio/Visual, thru Vmux	
	<b>SIRENS:</b>	1
DK-10-16SR	Siren, WHELEN,WS295SLSC1(REMOVABLE MIC) (1700300)	1
	in cab console	
DK-11-2706	Siren, Whelen, Howler installed, Intl 4300, IATS *Whelen Howler installed, IATS, (1) each side behind front bumper. *Activation/Cancellation 3-position momentary rocker switch installed on center console, on driver's side of siren. *Label: Activate-Howler-Cancel	1

PART NO	DESCRIPTION	QTY
	DELETED COMMENT: Customer wants to use OEM airhorn switch on steering wheel to activate howler.....	
	<b>AIR HORNS:</b>	1
	airhorns are ordered with chassis	
	<b>SWITCHING OPTIONS FOR AIR HORNS &amp; SIRENS:</b>	1
	Switch, Siren/Horn Thru Horn Ring, thru VMux	
DP-11-2500	Switches, Foot (2),(1) Dr Side,(1) Pass for airhorns	1
	<b>AUDIBLE ALARMS:</b>	1
F0-10-50SR	Alarm, Door or Comp Ajar in Gear, thru VMux (SO-AJAR-329016)	1
	Use #EL02948, BUZZER,A1-3238-TF-LW140-R ilos !!!!!	
F0-11-4500	Alarm, Back-up, Auto Reset, ILOS  thru VMux	1
	<b>VEHICLE EXTERIOR LIGHTING LIGHTBARS, WHELEN</b>	1
FA-11-SR00	LB, Whelen Mini-Freedom, (2), Angle Mounted on Cab Roof (SO-LB-299040) SR #214436F	1
	All lenses clear	
	(1) Angle mounted on street side cab roof, as outboard as possible, as far forward as possible (1) Angle mounted on curb side cab roof, as outboard as possible, as far forward as possible	
	SWITCHED: FRONT LB	
	White lights only Disabled in park / neutral	
	^^Production notice - make sure that the rear outboard flashing light is mounted outboard	
FF-10-6000	Cab Headliner Removal Fee, MAV for lightbar installation	1
	<b>LIGHT BAR, ARROWSTIK/TRAFFIC ADVISOR</b>	1
FF-13-SR02	LB, TA870L, All LED, 48" Long, 6 LED (SO-LBR-311195) SR #214436F	1
	(Only 6 lights due to length)	
	With arrows on end lights	
	(1) Rear of module, above rear entry doors, below warning lights !!!	
	Mount #TACTLD1 control modules in cab console	
	Clear lenses	
FU-35-SR03	Opticom, #76-1000-1157-0 with 2100 GPS radio 794HM emitter (SO-OPTI-341004) SR #213347F	1
	(1) #EL00172, OPTICOM EMITTER,794HM LED (1) #EL02340, GPS,76-1000-1160-0,SER 2000	

PART NO	DESCRIPTION	QTY
	Mount on the Coolbar centered to hang off the bottom of the cool bar, under red 9L light that is off center toward driver side.(not per drawings!) Use U bracket to install.	
	SWITCHED: Sep switch, Primary dependant.	
	<b>WHELEN M9 SERIES LED FLASHING LIGHTS:</b>	<b>1</b>
FU-41-0105	Light, M9RC, LED, Whelen, Red, Clear Lense, ILOS, W/Flange (2) Front of module, outer corners, standard locations	8
	(2) Curb side of module, standard locations	
	(2) Street side of module, standard locations	
	(2) Grille upper	
	SWITCHED: Primary / Secondary	
FU-41-0107	Light, M9RC, LED, Whelen, Red, Clear Lense, IATS, W/Flange (2) On front, on coolbar, IATS PATTERN: R,R,R,C,R,R,R SWITCHED: PRIMARY/SECONDARY	12
	(2) On front, on coolbar, IATS PATTERN: R,R,R,C,R,R,R SWITCHED: PRIMARY/SECONDARY	
	(2) On rear kickplate one each side SWITCHED: Primary / Secondary	
	(4) two on each side of module, inboard of upper each corner light, SWITCHED: Primary / Secondary	
	(2) on rear thru lower windows,(equally space w/ILOS lts) SWITCHED: Primary / Secondary	
FU-41-0110	Light, M9AC, LED, Whelen, Amber, Clear Lense, ILOS, W/Flange	1
FU-41-0111	Light, M9AC, LED, Whelen, Amber, Clear Lense, IATS, W/Flange (2) To show through center of rear windows SWITCHED: Amber light switch	2
FU-41-0114	Light, M9C, LED, Whelen, Clear, ILOS, W/Flange Center front, on coolbar SWITCHED: Primary	1
	<b>WHELEN 6E FLANGES:</b>	<b>1</b>
H2-10-0050	Flange, 6E Series, (1) each for turn signals on front	2
H5-58-0620	Light, M7RC, LED, Whelen, Red, Clear Lens, ILOS (2) Rear of module, outer corners, standard locations SWITCHED: Primary / Secondary	2
H5-58-0625	Light, M7RC, LED, Whelen, Red, Clear Lens, IATS (4) On Rear over rear doors, IATS PATTERN: R, R, R LD, A, LD, R, R, R SWITCHED: Primary / Secondary	6
	(1) on C/S entry door, same height at rear intersector SWITCHED: Primary / Secondary	
	(1) on compt "F" door, same height at rear intersector	

PART NO	DESCRIPTION	QTY
	SWITCHED: Primary / Secondary	
H5-58-0640	Light, M7AC, LED, Whelen, Amber,Clear Lens,ILOS (1)Center rear Amber	1
	SWITCHED: Primary / Secondary	
H5-58-0645	Light,M7AC, LED, Whelen, Amber,Clear Lens,IATS (2) one each side over rear wheel well SWITCHED: Amber light switch	4
	(2) lower grille SWITCHED: Amber light switch	
H5-58-0685	Light, M7D, LED, Whelen, R/C, Clear Lens,IATS (2) On front fenders as front intersector white portion of light to be toward the front SWITCHED: Primary / Secondary	2
	<b>WHELEN FLANGES 7 SERIES LIGHTS</b>	
H5-59-1000	Flange, Whelen, For 7E lights (1), Mods for rear load lights	2
H5-59-3135	Light, Whelen, M4D Red/ Clear, Lens clear w/ Flange, IATS	1
H5-59-500A	SKIRTRAIL WARNING LIGHTS	1
H5-59-50SR	HG2 Runner™ Lighting System, under modular body rubrails (SO-LT13-359007) SR #214436F	1
	Switched Prim only, wired per Engineering.	
	Lighting System - Four Section -	
	Two, (1) each side forward of rear wheels under skirtrail, approx 72" long, with Red / White / Red / White / Red / White / Red / White / Red / White / Red / White light sections: alternate flashing.	
	Two (1) each side rear of rear wheels under skirt rub rail, approx 42" long, with Red / White / Red / White / Red / White / Red sections, alternate flashing.	
H5-59-51SR	HG2 Runner Lighting System, under Cab (SO-HG2-359007) SR #213292F	1
	BOM Scarce: DELETE: #AS00296 ADD: #AS00297	
	Switched Prim only, wired per Engineering.	
	Note: complete kit(both sides) mounted under cab each side, Red/White Alternate flashing	
	<b>CORNER CAP LIGHTS</b>	
HF-11-6048	Corner Cap Lts,Multi-LED,(2)Amber(2)Red w/Flashers	1
	High intensity flashers, pri/sec ilos.	
	<b>CLEARANCE LIGHTS:</b>	
		1

PART NO	DESCRIPTION	QTY
HF-12-9600	Light, Clearance, Red LED, ILOS On rear as clearance lights.	3
<b>SCENE AND LOAD LIGHTS</b>		<b>1</b>
HK-20-13SR	Light, LED, Whelen, Clear, 12 Diode, Load Lights (SO-LT10-311195) SR #214436F	2
	Whelen #70C0ELZR Gradient Opti-Scene Light.	
	Two (2) Rear loads above !!! arrow stick	
HK-30-SR01	Light, PFP2 Dual panel LED Floodlight, ILOS (SO-LT11-311195) SR#213200F	2
	one each side centered	
	Switch as Right Scene, Left Scene	
	Set at 15 degrees	
<b>V-MUX ELECTRICAL SYSTEMS :</b>		<b>1</b>
J6-10-0350	V-MUX Electrical System, Vista IV, Non Touch, Int'l/Chev 4500, ILOS (SO-VMUX-359007) ***Engineering notice - use latest version per Service request. to include Vmux programming for HVAC to activate with engine start to high fan previous temp; mod power with engine start, add inverter switch to rear Vistas, remove O2 alarm CS Vista; amber warning to also activate with unit running & in park.	1
	Rear Warning Lights, Activation with Reverse Customer wants rear module warning lights to activate when unit placed in reverse.	
	Switching, Warning Lights, Additional Customer wants the Amber Warning lights to be switched with Emergency Master AND separately on Amber Switch if Emergency Master not activated. ILOS	
	Switch, Additional, For Amber Warning Lights in VMUX	
	(6) amber lights to be independent of all other lights For amber grilles, rear ambers at windows & rear intersector. Center rear amber is on warning light switch.	
	Auto Secondary, Neutral Safety, Custom To automatically shut off the following lights when vehicle transmission is placed in park: center white light, and white lights in lightbars on cab roof.	
	Circuit still gets the warning light switch & secondary override The secondary override switch is for the center white light.	
	White lights in lightbars will stay off until vehicle is placed back into gear.	
	Automatic Secondary, Neutral, W/ Switch Auto secondary to shut off center white light, (4)grille lights, center amber, and (2)front intersection lights, when vehicle is placed in neutral.	
	Scene Lights, C/S, Activated W/C/S Door	
	Side Scene Lts Activate W/Rev Gear.	
J6-10-0625	V-Mux, Swivel for Vista Display Mounting	1
	Must Verify with Engineering fit/function/use	

PART NO	DESCRIPTION	QTY
J6-10-0655	Camera, Backup, Rear Module Mounted Mount camera on rear of module, per pictures of Margate on server.(Bracket #B292455 is required)  V-Mux Vista in cab serves as monitor	1
J6-10-0675	V-Mux, Additional Vista IV, Non Touch Display in Str/s action area, IATS.  Mount on or beside "outlet panel".(Eng to recommend best location for approval prior to release)	1
J6-10-0800	Sensor, Exterior Temperature, V-Mux	1
J6-10-1000	V-Mux, Transducer for Pressure Monitoring Oxygen	1
J6-10-2000	V-MUX Electrical System, Engineering Programming -Hvac fan on hi with ignition -Mod power on with ignition -Amber light on automatically with ignition on and park neutral on, and also with the warning lights. -Remove o2 alarms from c/s vista	1
	<b>STOP/TURN/TAIL LIGHTS:</b>	1
JA-10-1200	Light, License Tag, (2), Trucklite #15205 LED, ILOS	1
JA-13-8012	Tailights, Whelen,LED Stop/Tail,Turn & LED Backup, w/ WC logo, ILOS - Brake- Alert Flash before the steady Burn - Turn Arrow – sequential arrow - Replace backup with 700 LED	1
JA-14-360E	Turn Signal, Whelen, Amber Arrow, 6LED, IATS, Pair Two (2) on front of module, one each side directly below outer warning lights FLASH: Sequential	1
JA-17-SR01	Turn/Brake/Turn Indicators, Custom (SO-IND-311195) SR #214436F  Peterson  (2) Amber lights in each group (1) Red lights in each group (1) Group of lights on forward facing wall, foot of S/B, near liner (1) Group of lights on face of bulkhead, up near liner.	2
JA-21-065E	Trn Sigl, Amber Turn, Whelen, 7L, IATS, Pair in angled housings, over and in front of the rear wheels.	1
JA-22-SR01	Housing,Cast,Angled,CO4500-3, Pair (SO-CAST-359007)  For 7L Amber Arrow turn signals rear wheelwell area	1
	<b>MODULE OVERHEAD HEADLINER:</b>	1
JK-10-5510	Headliner, Flat, Expanded PVC, 160"+ MAV/Type 1  Center ceiling wiring cover needs support brackets on driver side forward where wires go over toward action area.	1
	<b>12VDC INTERIOR LIGHTING:</b>	1
JP-10-0611	Lights, Dome, LED, Whelen,White Fing, (4) S/S, (3) C/S, ILOS NOTE: NO VISABLE FASTENERS OR HOLES.	1
JP-10-0621	Light, Dome, LED, Whelen,White Fing,(1) IATS in liner over C/S door stepwell, switched with right domes.	1



PART NO	DESCRIPTION	QTY
JP-10-7015	Light, Stepwell, LED, Whelen #TOCACCCR, 2in, ILOS Rubber Grommet Mounted in Stepwell- for lower step	1
JP-10-80SR	LIGHT,Tecniq #E20-WCOR, Red/White LED,IN Str/s AA, ILOS (SO-LT3-359007) SR212855F with (2) position switch in Str/s A/A.	1
JP-10-82SR	LIGHT,Tecniq #E20-WCOR, Red/White LED,IN Str/s AA, IATS (SO-AALT-311195) SR#212855F install under cabinet L1, IATS, inline with ILOS Str/s A/A light. Switch with existing Str/s A/A light.	1
JP-10-SR02	Light, Dome, Red/White, LED, #ECVDMLT2AL00 (SO-DOME1-311195) SR #214436F Mounted headliner between cab seats - see photo. Use the sw on the light to turn light on & off.	1
JP-10-SR05	Light, Door Ajar Indicator, #M162SR, 2" Red, Flashing, IATS (SO-LIGHT-359007) in center of overhead console at bottom, to activate whenever a module entry or compt door is open and vehicle is in gear, ignition hot. Label as "DOOR AJAR"(sticker on plate) Flash thru VMux.  (1) #AS82469, LIGHT,M1625R,LED (1) #AS82479, PLUG,B162-49  DELETED: (1) #EL33372, external flasher #SS245	1
<b>LIGHTS &amp; MISCELLANEOUS:</b>		1
JR-50-1000	Spotlight, Whelen LED, P46HHS 9 Diode hand held, ILOS (SO-SPOT-359007) SR#214300F on pass side of cab console, plugged into cig ltr outlet	1
JR-50-2700	Lights,(2), 4in, LED, to Illum Running Boards Activated with the cab doors. Connected to cab dome light circuit.	1
JR-50-2885	Lighting, Compt, LED Hi-Brite Flex, ILOS both vertical edges near door jambs and across top edge near door jamb, compts "A", "B2", "D", "E", "F", and on bottom of closeout in compt "A".  Install short strip of LED lighting for "O2 light", activated on right dome high intensity circuit, ILOS. Light to be mounted on wall #1, just above level of O2 rack.  DELETED COMMENT: Lighting on wall #3.....	1
JR-50-SR00	Light, Whelen #50A00FCR, Amber, Clear Lens, Internal Flasher (SO-LT13-311195) SR #214436F Engineering & Production reference only #299040  (1) Mounted near bottom of C/S entry door panel, lower right. (1) Mounted near bottom of C/S rear entry door panel, lower right.	5

PART NO	DESCRIPTION	QTY
	(1) Mounted near bottom of Str/S rear entry door panel, lower left.	
	(2) Mounted on cab doors, interior panel.	
	Ignition switch hot FLASH: Single flash as rapidly as possible Each light should only flash when that specific door is open	
JR-60-2006	Timer, Momentary Sw, 15 Minute, Constant Hot, MAV LOCATION: Bulkhead Wall Near C/S Entry Door WIRED TO: (4) curbside dome lights, high intensity  Switch to allow activation and also deactivation	1
	<b>CLOCKS:</b>	1
L0-10-1500	Clock, Analog, Self Cont, 12/24 Hr, 8", w/Second Hand  LOCATION: on wall at foot of S/B, per drawings.(see next option for custom mounting instructions)	1
L0-10-SR01	Custom Mounting of Clock (SO-CLOCK-329016) SR #210885F  Custom Mounting of Clock- Mount on a hinge with a velcro closure to allow for time and battery changes	1
	<b>INTERCOMS:</b>	1
LF-10-SR00	Intercom, Firecom, Model #5200D, (6) Position (SO-COM-359007) SR #214436F  Firecom #5200D Intercom System (6)Position - only 4 transmit) Dual Radio Interface  (1) #5200D mounted in cab console,  (6) HM-10 plug in modules: (1) cab ceiling, toward rear, off center toward driver's side, (1) cab ceiling, toward rear, off center toward pass side, (1) A/A - DELETE THIS LOCATION, ON 369004-5 and 369009. INSTALL CS REAR WALL UNDER SPLINT CABINET - SEE PHOTO FOR REFERENCE, (1) C/S wall at head of S/B, up high, (1) rear A/A under electric strip outlet with hanger (1) Adjacent to forward facing attendant seat  (6) Hanger hooks #520-0676-00 (2) cab ceiling,(1)outboard of each HM-10, (1) rear A/A, per picture. (1) C/S wall at head of S/B, up high. (2) ship loose for customer to install  (1) #108-0102-00, 6-conductor flat cable spool  (3) FH-51 dual muff radio transmit (3) FH-51S single muff (Note to Electrical Engineering - disable the PPT function of two of the Headsets when installing)  Interface Cable #MR52X- for Motorola XLT5000. Connect to "A" on Firecom 3020 in cab console. Radio installer will terminate the other end.  move headset jack and hanger to rear A/A under electric strip outlet  Add: (1) HM-10 plug in module,CS rear below splint cabinet, wired in parallel with other module on	1

PART NO	DESCRIPTION	QTY
	C/S wall and hanger. (1) EL39997 HEADSET MODULE HM-10 (1) EL38116 HANGER,HEADSET FIRECOM #HGR-1	
	<b>SUCTION PUMPS:</b>	<b>1</b>
	Std suction pump is deleted	
	<b>INSULATION:</b>	<b>1</b>
LU-10-3001	Insulation, Severe Weather Package one inch block foam in modular walls and roof covered with reflective insulation. Under Floor to be Spray Foam insulated after the production assembly process is complete by 24/7.  All edges of reflective insulation on walls and ceiling must be taped, std.	1
	<b>OVERHEAD GRABRAIL:</b>	<b>1</b>
N0-10-9100	Grabrail, Overhead, 117 In, Handicap Style, Yellow  Yellow Powder Coat Finish	1
N0-10-9704	Handrails,(3),Custom "L" Shape,1",Yellow,Entry Drs For units with Trimark handles.  Yellow Powder Coat Finish Stainless Steel Grab Handles	1
	ILOS	
N0-11-2100	Grabhandle, Black Spring style, (1), IATS (2), one each side by rear entry doors ref pictures of Winter Park  (1) near C/S entry door CS entry adjacent to A comp - see photo	3
	<b>O2 CYLINDER RACKS:</b>	<b>1</b>
NA-10-1500	Rack, Versatile, "M" Or "H", ILOS	1
	<b>STRAPS, O2:</b>	<b>1</b>
NA-30-2800	Strap, Cylinder, Ratchet Style, (3) Each, ILOS	1
	<b>O2 SYSTEMS COMPLETE:</b>	<b>1</b>
NK-51-2500	O2 Sys,LF Stor,2-AA Elec,No-VAC,1-C/S,1-Liner (SO-O2-359007)  ohio style electric switch w/bypass in action area (2) oxygen outlets in action area (1) oxygen outlet in liner at head of cot (1) oxygen outlet cs wall at head of squad bench	1
	<b>O2 SYSTEM PARTS:</b>	<b>1</b>
P0-59-7500	Regulator, Oxygen Cylinder, Preset 50PSI, Installed	1
	<b>SUCTION CONTAINERS:</b>	<b>1</b>
PA-10-8200	Suction Unit, Self contained, Impact #324, ILOS  Recessed cabinet "P" area.(Eng to reference drawings)	1
	<b>COT MOUNTS:</b>	<b>1</b>
PF-26-3100	Cot Mount, Stryker #6377, Dual Position - Change Notice 8- NOT COMPLIANT Set up for Power-PRO	1
PF-35-4200	Cot Mount, Stryker, Mods, Rear Safety Hook Installed	1
	<b>COT PLATES:</b>	<b>1</b>
PK-40-5800	Cot Plates, Stryker Cot, Dual Mount	1
	<b>IV HOOKS:</b>	<b>1</b>
PP-20-1000	IV Hook, Perko, (1), W/Straps, STD (1) on forward facing wall in front of cabt "K", per picture. This	2

PART NO	DESCRIPTION	QTY
	location will allow door on cabt "K" to open. (1) on C/S wall at head of S/B, per picture.	
PP-20-9000	IV Hook, Cast, Fold Down Recessed, IATS IV2 SS and IV2 CS	2
	<b>KICK PLATES STAINLESS STEEL, ON CABINETS:</b>	1
PU-10-1000	Kickplate, Brushed S/S, Face Of Squad Bench	1
PU-10-2000	Kickplate, Brushed S/S, On Face of Basewall	1
PU-10-3000	Kickplate,Brushed SS, on Forward Side of RF Cabt	1
	<b>MISC. INSTALLED HARDWARE/EQUIPMENT:</b>	1
R5-10-8000	Wrench, Oxygen, Tethered, Mods Install in Compt "F" Next to Bottle	1
	DELETED COMMENT: Velcro to wall.....	
R5-10-SR02	Bracket for Lifepak 12/15, Ferno #M200 SO-M200-331034) Ref (SO-M200-299031) SR#213254R-1	1
	Extended action area - see photo	
R5-11-SR01	Bracket, Zico, SCBA, Angled, for Scott 4500 PSI Cylinder (SO-BRACK-311072)	3
	(1) Zico Model SC-50-H-5-SF bracket with Zico Model CRS strap on Zico Model ABS angled bracket. Compt "A", wall #1, approx 6" above floor(ABS Bracket), on plate mounted to shelf track. Make certain the SCBA is angled toward the outside of the compartment.	
	(1) Zico Model SC-50-H-5-SF bracket with Zico Model CRS strap on Zico Model ABS angled bracket. Compt "F", wall #1, approx 16" above floor(ABS Bracket). Make certain the SCBA is angled toward the outside of the compartment. **NOTE - Change in height(starting with #321185)	
	(1) Zico Model SC-50-H-5-SF bracket with Zico Model CRS strap on Zico Model ABS angled bracket. Compt B, wall #1 wall #1, approx 6" above floor(ABS Bracket). Make certain the SCBA is angled toward the outside of the compartment. (note - wall previously reinforced)	
	<b>DRI-DECK/TURTLETILE:</b>	1
RA-10-2000	Dri Deck, Black, All compt. Floors and Shelves	1
	<b>STRAPS, INSTALLED:</b>	1
RK-13-3500	Seat Belt, Across Compt Opening	1
	compt "D", wall #1 to fixed divider, mid height, for stairchair and backboards.	
	<b>MODULE INTERIOR</b>	1
RU-05-0000	Interior Cabinets - Duralite Construction, Wood	1
	<b>MICA COLOR:</b>	1
RU-14-1900	Mica,Dove Gray Over Pewter Brush	1
	<b>SUB FLOORING:</b>	1
RZ-99-0100	Floor, Interior, Non Wood, Type 3/9, ILOS	1
	<b>FLOORING:</b>	1
T0-11-8200	Flooring, Lonplate II,Gunpowder Grey #424TX, ILOS	1
	<b>SEAMLESS ATTENDANT SEATS:</b>	1
T5-10-10SR	'Seat, EVS Tri-Star, Gunmetal, 5-point, ILOS (SO-SEAT1-311195) SR #214436F	3
	(2) ILOS on squad bench seating, the two rear seat positions.	
	(1) CPR Seat	
	YELLOW SEAT BELTS, ILOS !!!!!	
	<b>ATTENDANT SEATS</b>	1
T5-10-SR00	Seat, Attendant, EVS, Child,Gunmetal, #18805, 5-point, ILOS (SO-SEAT1-359007) SR #214436F	1

PART NO	DESCRIPTION	QTY
	YELLOW SEAT BELT, ILOS !!!!!	
	(1) Vacuum formed EVS18805 w/ 5 point seatbelt. Integrated child safety seat, Mounted on fixed seat base at front of cot position.	
T5-10-SR01	Seat, Attendant, EVS, Child, Gunmetal, #18805, 5-point, IATS (SO-SEAT-359007) SR #214436F	1
	YELLOW SEAT BELT, ILOS !!!!!	
	(1) Vacuum formed EVS18805 w/ 5 point seatbelt. Integrated child safety seat, Mounted on fixed base at front of attendant seat position to face forward .	
	<b>SEAMLESS UPHOLSTERY:</b>	1
T5-25-0500	Uph, Smless, Gunmetal, No Bio, No Post & Wheel Add upholstered pad to left basewall forward of A/A between headset jack and brushed mica surface. Add upholstered pad on right side of pass-thru like strip on upper surface.  Use screws/button caps	1
	<b>BULKHEAD CABINET:</b>	1
TF-50-SR00	Bulkhead, Custom (SO-BH-359007) SR #212855F  HVAC relocated to left front corner Streetside angled. Walk-thru opening as large as possible, note relocated RF compt "A"  Eng: ref Sarasota for required height and width of opening.  Pass-thru "step" needs a 90 degree kickplate cover - suggest ADP painted with dark scorpion	1
	<b>O2 DOOR:</b>	1
TK-10-5000	Lexan Flap W/Hinge	1
TK-10-SR01	Custom O2 Door 3/8" Lexan - Tethered - Finger Hole (SO-O2WIN-359007) SR212855F  A/A Wall #3 Finger Hole Opening with Magnet Hold Close Latch. Shall be tethered with stainless steel cable with Perko Clips	1
	<b>GLOVE HOLDERS:</b>	1
TN-20-1001	Cabinet, Glove Box Holder, (3), Above C/S door, Std Model only	1
TN-20-1001	Cabinet, Glove Box Holder, (3), Above Rear Doors (SO-GLOVE-359027) SR #215168F	1
	<b>RIGHT FRONT CABINET:</b>	1
TU-19-SR10	Cabinet, RF, Combo, EMS MAV, Custom, Relocated to SB (SO-RF-359007) SR212855F  Standard RF Delete ILO of C/S entry door moved forward, moved to rear of CS entry door	1
	<b>RF CABINET DOORS</b>	1
TU-21-SR01	Custom Right Front Cabinet Door (SO-ROM-359007) SR #212855F  Shutter series 3 style door per Mech Eng ! ROM roll-up door, sill plate with dam, NO pull strap, satin finish, Top/Front style collector roll for the door. NO lock on door  Eng Note - Cover for drum Eng print 346987	1

PART NO	DESCRIPTION	QTY
<b>LEFT FRONT CABINET:</b>		
TU-50-2100	Cabinet, Left Front, EMS F/R, MAV, W/72" H.R. (SO-LF-359007)	1 1
	Angled cabt behind attendant's seat for circuit board, below angled heat/ac unit.	
	Door on LF cabt to be lift off and removable due to placement of addt'l attend seat.	
V0-11-5000	Latch, Lever, No Key, STD, Installed for removable LF cabt door.	2
V0-14-2077	Latch, Southco M1-64-8, 2IN S/S, Non-Locking, (1), IATS self latching, Flush Mount. Non-Locking	3
	(1) - DR1 drawer, head of SB (1) - DR2 drawer, head of SB (1) - BIO drawer, head of SB	
V0-14-2078	Latch, Southco M1-62-8, 2IN S/S, Non-Locking, (1), ILOS self latching, Flush Mount. Non-Locking	2
	Cabt "R1" & "R2"	
V0-14-21SR	Latch, Southco M1-63-8, 2IN S/S, Non-Locking, (1) (SO-LOCK2-303066)	1
	Cabt "J", 1/2" lexan door.	
<b>SQUAD BENCH:</b>		
V5-20-14SR	Squad Bench, Custom (SO-SB-359027) SR #211949F new code	1 1
	Squad Bench to use (2) Tri-Star seats at rear of bench. Forward Seat area to lift up for storage underneath. This to have binning strips with (4) dividers. Binning strips will be on wall #1 and wall #3. Rear S/B lid to lift up for access to seatbelt mounting points.	
	No inside/outside access to compt B. Cabinet at front of bench with slide out bio waste into aisle - Two drawers above bio waste which will slide out into aisle approx 6" high x 13" wide x 15" deep(?) - mica top with 1" lips.	
	See reference CAs.	
	Eng Note: starting after unit #359007 customer wants to reduce depth of S/B approx 1" to increase aisle space.	
<b>LID 170 INCH BOX:</b>		
V5-64-05SR	Lid, Squad Bench, Custom (SO-SBLID-359027) new code !!	1 1
<b>HARDWARE:</b>		
V5-80-1005	Handle, Trimark, Squad Bench, STD	1
V5-80-43SR	Grabber, Mini, #DH0046-5, Installed (SO-HOLD-311203) #CA46030	2 1
	for forward S/B lid - location as per CAs..	
V5-82-1500	Strut, Gas, 20 LB, Installed, IATS (SO-STRUT-359007)	2
	for cabinet J door	
<b>CURBSIDE SPLINT CABINET</b>		
		1

PART NO	DESCRIPTION	QTY
VA-40-SR01	Splint Cabinet Above Curbside Squadbench (SO-CSU-359007) SR #214436F	1
	Splint Cabinet Above Curbside Squadbench	
	with exhaust fan to rear of cabt "R2"	
	3/8" Lexan Lift Up Doors shall have full length polished(or brushed) aluminum "cap" on the Hinge Side with a full length Piano Hinge.	
	No Holdopens.	
	Fresh Air intake vent and Aux Vista panel at head of SSU cabt.	
	<b>CURBSIDE REAR CABINET:</b>	1
VF-20-6100	Cabinet, Curbside Rear,no B2,Rear wall only	1
	<b>CABINET H, BASEWALL, 170", T9</b>	1
VH-H4-0400	H, Cabinet, Deleted	1
	<b>CABINET I, BASEWALL 149/153", T1 &amp; T3</b>	1
VH-I0-0400	I, Cabinet, Deleted	1
	<b>CABINET CPR, BASEWALL, 160" &amp; 170", T9</b>	1
VH-Q1-SR00	CPR, side seat, Custom, (SO-CPR-359007) SR #214436F	1
	*CPR seat mounted aft of std location with Tri-Star seat (seat priced elsewhere)	
	with Trimark handle.	
	<b>CABINET J, STREETSIDE UPPER 149/153", T1 &amp; T3</b>	1
VI-J2-SR00	J, Cabinet, Custom (SO-J-359027)	1
	This area designed for Danhard AC system.	
	<b>CABINET K, STREETSIDE UPPER 149/153", T1 &amp; T3</b>	1
VI-K2-SR00	K2, Cabinet, Custom (SO-K2-359007) SR #212855F	1
	Cabinet over CPR Side Seat Cabinet shall be 9"H interior(8"H passthru) x 19" W x 13.75" Deep.	
	3/8" Lexan Lift Up shall have full length polished(or brushed) aluminum "cap" on the Hinge Side with a full length Piano Hinge. Gas Strut Holdopens (2)	
	<b>CABINET K, STREETSIDE UPPER 160" &amp; 170", T9</b>	1
VI-K3-SR00	K, Cabinet, Deleted	1
	<b>CABINET L, STREETSIDE UPPER 160" &amp; 170", T9</b>	1
VI-L2-SR00	L, Cabinets, Custom (SO-L-359007) SR #213314	1
	Custom "L" cabinets - Modify L-1/L-2 for the Heat/AC above compartment "F"	
	<b>CABINET OPTIONS:</b>	1
VK-11-0ESR	Cabinet Doors, Glass Beaded Gray Lexan Slider (SO-BEAD-311195) SR# 210826F	7
	Glass beaded on backside of lexan only on following cabinets: K2, L1, L2, R1, R2	
	O2 window flaps	

PART NO	DESCRIPTION	QTY
VK-17-6200	Restocking Feature, (1) cabinet, (2) Gas Strut, 20lbs,ILOS L1 & L2	2
	With 2 Perko elbow latches for closure.	
	installed on the following cabinets:	
	<b>ACTION AREA WORK SURFACE</b>	1
VP-11-SR01	Tray, A/A, Stainless Steel, ILOS (SO-TRAY-359007) SR #212855F	1
	Tray will have a 1.5" high lip on all sides. Custom A/A length	
	<b>ACTION AREA CABINET:</b>	1
VP-15-9500	Cabinet, A/A, EMS MAV, No Biowaste	1
	with rounded corner package	
VU-14-4000	Shelf, Interior, Adj, in Cabinet:	2
	(1) each in cabts "L1" & "L2"	
VU-14-4001	Shelf Track, Cabt, #HA24663, Upgrade, Std Model only ("C" channel/exterior shelf style track)	2
	(1) each in cabts "L1" & "L2"	
VU-15-6000	Cab "K2" Gray Lexan Slider	1
VU-15-8000	Cab "L1" Gray Lexan Slider	1
VU-16-3000	Cab "L2" Gray Lexan Slider	1
	<b>SHIP LOOSE ITEMS:</b>	1
YY-10-6400	Ship Loose, W.C. Standard Items	1
	<b>WARRANTIES</b>	1
ZZ-10-0600	Warranty, Limited Lifetime Electrical	1
ZZ-10-1900	Warranty, Lifetime, Mod Structural	1
ZZ-10-2000	Warranty, Limited Lifetime, Mod Paint	1
ZZ-10-2200	Warranty, Extended, 5 Year/100K Miles, Types 1, 3, 9 (WARR1-359007)	1
ZZ-10-50SR	Warranty, Chassis, Extended, 5 Year/100K miles (WARR2-359007)	1
	Policy Number B1015C/0040EMV 60-Month/100,000 Miles (160,000 km); With 90-Day Towing; Covers 100% Parts and Labor, Excludes Extending Warranty for Engine, Frame Side Rails, Paint, Perforation or Corrosion of Cab/Cowl Structure	
	<b>EMS SUPPLIES SHIP LOOSE</b>	1
	(EMS-359027)	
ZZ-25-0525	CYLINDER, "M", ALUMINUM	1
ZZ-25-0595	FLOWMETER, FLOWTECH, F10-3EOP6	3
ZZ-25-1020	REGULATOR, OXYGEN, FLOWTECH, #RR830-340P2 shipped loose	1
ZZ-26-0005	Life Pak 15 (EMS _____) SR #2131054R-1	1
	Life Pak 15 - #99577-001256; #11577-000004; #21330-001176 (qty4); #11171-000049; #11160-000007; #11577-000002;	



PART NO	DESCRIPTION	QTY
	#11220-000028; # 11260-000039; #11160-000003; #mc999-001005-5-pos	
ZZ-26-0010	Zoll Autopulse (EMS _____) SR #214365R-1	1
	Zoll #8700-0730-01 AutoPulse® System with Pass Thru - Includes Backboard, User Guide, Quick Reference Guide, Shoulder Restraints, Backboard Cable Ties, Head Immobilizer, Grip Strips, In-service Training DVD, and one year warranty.	
	#8700-0752-01 AutoPulse® Li-Ion Battery - for use with the AutoPulse Platform. #8700-000758-01 AutoPulse® Soft Carry Case - with battery pocket #8778-008730 Multi- chemistry Charger 2 Year Extended Warranty, includes three (3) Li-Ion batteries (at time of equipment sale), #8778-8704 AutoPulse 4 Year Extended Factory Warranty	
ZZ-26-0025	Scott SCBA # #AP2140203200402 Scott 4.5 AP75 (EMS _____) SR #2131054R-1	3
	Scott SCBA #AP2140203200402 Scott 4.5 AP75, CBRN/SH/SEM/DEBSS Pass Device	
ZZ-26-0030	Scott Eagle Attack, Black Bumper (EMS _____) SR #2131054R-1	1
	Scott Eagle Attack, Black Bumper, Fahrenheit Thermal Imaging Camera mode TCS Accy Kit	
ZZ-26-0035	Scott Eagle #200977-01 Attack Charger less Cables (EMS _____) SR #2131054R-1	1
	Scott Eagle #200977-01 Attack Charger less Cables	
ZZ-26-0040	Stryker Stair-PRO #6252, w/options (EMS _____) SR #2131054R-1	1
	Stryker Stair-PRO #6252, standard features plus #6252-025-000 IV pole clip, #6252-040-000 removable head support, #6250-140-000 O2 bottle holder	
ZZ-26-0045	Insight Panasonic Toughbook 31 (EMS _____) SR #2131054R-1	1
	Insight Panasonic Toughbook 31, Win7, Intel Core i3-3110M 20,835.00 2.40GHz, No vPro, 13.1 XGA Touch, 320GB(5400rpm),2GB, Intel WiFi a/b/g/n, No TPM,Bluetooth, Lightweight Battery, Dual Pass (Upper:WWAN/Lower:Selectable), Verizon 4G LTE, Emissive Backlit Keyboard, No Drive,Toughbook Preferred	
ZZ-26-0050	Stryker #6506 Power-PROXT Cot, w/options (EMS _____) SR #214308F	1
	Stryker #6506 Power-PRO XT Cot, standard features plus #6500-215-000 3-Stage IV pole patient right, #6500-147-000 Equipment hook, #6500-700-011 Fowler oxygen bottle holder with pad, #6500-130-000 backrest storage pouches, #6500-128-000 flat head storage pouch, #6506-040-000 XPS (expandable patient surface) #6500-028-000 120V AC power cord, #6500-034-000 SMRT™ mounting bracket.	

